

### Stainless Steel Metal Hose Specifications

ID Size (in.)	Product Designation	Max. Oper. Pressure (PSI)	Max. Test Pressure (PSI)	Min. Burst Pressure (PSI)	Static Bend Radius (in.)	Dynamic Bend Radius (in.)	Outside Diameter (in.)	Wt. Per Foot (lbs)
1/4	MDS6	3250	4875	13,000	3	6	0.62	0.3
0.375	CF04/CF16	1450	2175	5800	1.15	6	0.7	0.23
1/2	CF04/CF16	1375	2063	5500	1.75	5	0.8	0.24
0.75	CF04/CF16	725	1088	3500	2.1	7	1.15	0.36
1	CF04/CF16	580	870	2400	2.5	7.7	1.49	0.44
1¼	CF16	580	870	2320	3.1	9	1.8	0.68
1½	MSS4	560	1120	2240	3.5	10.5	2.2	1.8
1½	CF16	435	870	1740	4.75	9.5	2.1	1.09
2	MSS4	525	1050	2100	4.5	12	2.72	2.37
2	CF16	500	1000	2000	6	11.5	2.7	1.55
2½	MSS4/MSS6	380	760	1520	5	13	3.5	2.7
3	MSS4	285	570	1140	7.5	16	4	2.87
3	CF16	350	750	1400	8	16	3.9	2.7
4	MSS4	250	375	1000	10	20	5	4
4	MSS6	275	550	1100	9	20	5.1	3.9
5	MSS4/MSS6	275	450	900	12	24	6.25	6.66
6	MSS4/MSS6	200	400	800	15	30	7.3	7.8
8	MSS4/MSS6	185	370	740	20	40	9.45	10.8